

# H 15 D

## Hydrostatic

### 2WD & 4WD

# mast<sup>®</sup> EXPLORER

## Rough Terrain

# H 15 D

### Características Técnicas Technical Details

### Technische Daten Caractéristiques Techniques

Capacidad Nominal Nominal Capacity	<b>1500 kg 3000lb</b>	Capacité Tragkraft
Centro de Carga Load Center	<b>500 mm 24" for data in lb</b>	Centre de Charge Lastschwerpunkt
Motor Diésel Diesel Engine	<b>Perkins 404C.15 4 cil. / 36 hp</b>	Moteur Diésel Diesel Motor
Transmisión Hidrostática Hydrostatic Transmission	<b>Automotive HP</b>	Transmision Hidrostatique Getriebe Hydrostat
Mástiles Dúplex Two Stage Masts	<b>2,7 m* 9,0 ft*</b>	Mâts Duplex Duplex Mast
Mástiles Tríplex Three Stage Masts	<b>3,7 m 12,0 ft</b>	Mâts Triplex Triplex Mast
Portahorquillas Forks Carriage	<b>FEM II B</b>	Tablier Gabelträger
Desplazador Integrado Integrated Sideshift	<b>Standard</b>	TDL Intégrè Eingebaut Seitenschieber
Pendiente Superable Gradeability	<b>35%</b>	Pente supérable Ersteigbarer Hang
Peso Total Total Weight	<b>4x2 3000 kg 6614 lb 4x4 3100 kg 6834 lb</b>	Poids Total Gewicht

\*Mástil Estandar, Standard Mast, Mât Standard.

### Especificaciones técnicas Technical Specifications

### Maschinenmesstechnik Specifications Techniques

A	Longitud total Total length	<b>2500 mm 98 in</b>	Longueur totale Länge
B	Distancia entre ejes Axles distance	<b>1480 mm 58 in</b>	Distance entre essieux Entfernung zwischen Achsen
C	Distancia de carga Load distance	<b>420 mm 17 in</b>	Distance de charge Last Abstand
D	Voladizo trasero Rear projection	<b>600 mm 24 in</b>	Porte a faux arriere Rückprojektion
E	Altura libre al suelo Ground clearance	<b>270 mm 11 in</b>	Hauteur libre au sol Bodenfreiheit
F	Altura total Total height	<b>2000 mm 79 in</b>	Hauteur totale Höhe
G	Anchura total Total width	<b>1380 mm 54 in</b>	Largeur totale Breite
H	Radio de giro Turning radius	<b>4x2 2750 mm 108 in 4x4 3550 mm 140 in</b>	Rayon de braquage Wendelgang Breite

